# Light Source, Power Meters and VFL



## ■ FEATURES\_\_\_\_\_

Wavelength:800~1700nm

Calibrated wavelength(nm):850,980,1300,1310,1490,1550

Power supply:3pcs AA 1.5V battery

Measurement range -50~26dbm is Available

With FC-SC Adaptor and FC-ST Adaptor

Model

Description

MPL-33P

Measurment Range: -10 ~ -5dBm





#### ■ FEATURES\_\_\_\_\_

With FC-SC Adaptor and FC-ST Adaptor

Emitter type:FP-LD

Power supply:3PCS AA 1.5V battery-Power supply:3pcs AA 1.5V battery

850/1300/1310/1490/1550 wavelength is Available

 Model
 Description

 MPL-50S-A
 For 1310/1550 Wavelength

 MPL-50S-B
 For 1310/1490/1550 Wavelength

 MPL-50S-C
 For 850/1300/1310/1550 Wavelength





### ■ FEATURES\_\_\_

With FC-SC Adaptor and FC-ST Adaptor

Light Source For 1310/1550 Wavelength"

Model
MPL-68PS

Description

Power Meter, Light Source

#### **MPL-1VPS**



#### FEATURES \_\_\_\_\_

With FC-SC Adaptor and FC-ST Adaptor

Light Source For 1310/1550 Wavelength"

Model

Description

MPL-1VPS

Power Meter, Light Source and VFL