

Network Switches

FEATURES

Port Features

Auto negotiation and auto MDI/MDIX

Switching Features

Store and forward switching method

Full duplex flow control and half duplex backpressure

Mac address auto learning and auto aging

LED indicators for monitoring power, link/activity, speed

Supports IEEE802.1Q VLAN, 4K VLAN Table

Support QoS, Port Mirroring, Link Aggregation Protocol

Management

Web-Based Management Supports

Support SNMP/RMON/TELENET

Console Port



Auto-Negotiation



Auto detect MDI/MDIX



Half-duplex & Full-duplex Mode



150m Transmission distance



Fast Ethernet Switch (10/100Mbps)



2SFP Slots



Web Management



Qos (Quality over service)



Port Isolation



Bandwidth Control



TECHNICAL SPECIFICATION

Model No.	SW-MNG-24GE4/10GSFP
Product description	24 Ports 10/100/1000Mbps + 4 port 10Gbps SFP
Chipset	BCM53346+BCM53344+2*B50282
10/100Mbps RJ45 Ports	NA
10/100/1000Mbps RJ45 Ports	42
1000Mbps SFP Ports	NA
10Gbps SFP ports	4
Console Port	1
PoE Ports	NA
Standards	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3ae, IEEE802.3x, IEEE802.3z, IEEE802.3ad, IEEE802.1P, IEEE802.1Q
Switching Fabric Capacity	136G
Mac Address Table	16K
Buffer	1.5MBytes
Jumbo Frame	12KBytes
IEEE802.3af	NA
IEEE802.3at	NA
Power Supply	100~240VAC,50/60HZ,48W, internal power
Max PoE Output Power	NA
Housing	Metal Rack Mount
Dimension	440 x 208 x 44 mm