

Network Switches

FEATURES

Port Features

Auto negotiation and auto MDI/MDIX

Switching Features

Store and forward switching method

Full duplex flow control and half duplex backpressure

Mac address auto learning and auto aging

LED indicators for monitoring power, link/activity, speed

Management

Unmanaged (Plug and Play)



Auto-Negotiation



Auto detect MDI/MDIX



Half-duplex & Full-duplex Mode



150m Transmission distance



PnP Switch (Plug and Play)



TECHNICAL SPECIFICATION

Model No.	SW-UNM-16FE
Product description	16 Ports 10/100Mbps Ethernet Switch
Chipset	IP1717+IP108A
10/100Mbps RJ45 Ports	16
10/100/1000Mbps RJ45 Ports	NA
1000Mbps SFP Ports	NA
Console Port	NA
PoE Ports	NA
Standards	IEEE802.3, 10Base-T, IEEE802.3u 100Base-TX
Switching Fabric Capacity	3.2Gbps
Mac Address Table	4K
Buffer	4.1Mbps
Jumbo Frame	10KByte
IEEE802.3af	NA
IEEE802.3at	NA
Power Supply	Input: 100-240V 50-60Hz 0.3A Consume: 7 W (MAX)
Max PoE Output Power	NA
Housing	Metal Rack Mount
Dimension	440 x 208 x 44 mm