

Network Switches

FEATURES

Port Features

Auto negotiation and auto MDI/MDIX

Switching Features

Store and forward switching method


Full duplex flow control and half duplex backpressure

Mac address auto learning and auto aging

LED indicators for monitoring power, link/activity, speed

Management

Unmanaged (Plug and Play)



Support
IEEE802.3af/3at
(30W each port)



Auto-Negotiation



Auto detect
MDI/MDIX



Half-duplex &
Full-duplex Mode



150m Transmission
distance



Fast Ethernet
Switch
(10/100Mbps)



PAP Switch (Plug
and Play)

TECHNICAL SPECIFICATION

Model No.	SW-UNM-16FE1GC
Product description	16 Ports 10/100Mbps +1 PORT 1000Mbps combo
Chipset	RTL8382M + RTL8218B+ RTL8231
10/100Mbps RJ45 Ports	16
10/100/1000Mbps RJ45 Ports	1
1000Mbps SFP Ports	1
Console Port	NA
PoE Ports	24
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z, IEEE802.3az
Switching Fabric Capacity	5.2G
Mac Address Table	4K
Buffer	4.1Mbps
Jumbo Frame	10KByte
IEEE802.3af	NA
IEEE802.3at	NA
Power Supply	Input:100V~240V AC 50/60Hz
Max PoE Output Power	NA
Housing	Metal Rack Mount
Dimension	441x208x44.3mm