

Network Switches

FEATURES

Port Features

Auto negotiation and auto MDI/MDIX

Switching Features

Store and forward switching method


Full duplex flow control and half duplex backpressure

Mac address auto learning and auto aging

LED indicators for monitoring power, link/activity, speed

Management

Unmanaged (Plug and Play)



Support
IEEE802.3af/3at
(30W each port)



Auto-Negotiation



AUTO
Auto detect
MDI/MDIX



Half-duplex &
Full-duplex Mode



150m
Transmission
distance



Fast Ethernet
Switch
(10/100Mbps)



PAP Switch (Plug
and Play)



TECHNICAL SPECIFICATION

Model No.	SW-UNM-16FE2GC-16POE
Product description	16 Ports 10/100Mbps PoE + 2 port 10/100/1000Mbps Combo Ethernet Switch
Chipset	RTL8332L + RTL8208L + RTL8212B
10/100Mbps RJ45 Ports	16
10/100/1000Mbps RJ45 Ports	2
1000Mbps SFP Ports	2
Console Port	NA
PoE Ports	16
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z, IEEE802.3az, IEEE802.3af, IEEE802.3at,
Switching Fabric Capacity	7.2Gbps
Mac Address Table	8K
Buffer	4.1Mbps
Jumbo Frame	10KByte
IEEE802.3af	✓
IEEE802.3at	✓
Power Supply	AC 100V-240V 50/60HZ (330W)
Max PoE Output Power	320W
Housing	Metal Rack Mount
Dimension	440 x 208 x 44 mm