

Network Switches

FEATURES

Port Features

Auto negotiation and auto MDI/MDIX

Switching Features

Store and forward switching method

Full duplex flow control and half duplex backpressure

Mac address auto learning and auto aging

LED indicators for monitoring power, link/activity, speed

Management

Unmanaged (Plug and Play)



**Support
IEEE802.3af/3at
(30W each port)**



Auto-Negotiation




**Auto detect
MDI/MDIX**




**Half-duplex &
Full-duplex Mode**



**150m Transmission
distance**



**Fast Ethernet
Switch
(10/100Mbps)**



**PAP Switch (Plug
and Play)**

TECHNICAL SPECIFICATION

Model No.	SW-UNM-24FE2GC-24POE
Product description	24 Ports 10/100Mbps PoE + 2 port 10/100/1000Mbps Combo Ethernet Switch
Chipset	RTL8332L + RTL8208L + RTL8214B
10/100Mbps RJ45 Ports	24
10/100/1000Mbps RJ45 Ports	2
1000Mbps SFP Ports	2
Console Port	NA
PoE Ports	24
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z, IEEE802.3az, IEEE802.3af, IEEE802.3at,
Switching Fabric Capacity	12.8Gbps
Mac Address Table	8K
Buffer	4.1Mbps
Jumbo Frame	10KByte
IEEE802.3af	✓
IEEE802.3at	✓
Power Supply	AC 100V-240V 50/60HZ (400W)
Max PoE Output Power	380W
Housing	Metal Rack Mount
Dimension	440 x 208 x 44 mm