

Network Switches

■ FEATURES____

Port Features

Auto negotiation and auto MDI/MDIX

Switching Features

Store and forward switching method

Full duplex flow control and half duplex backpressure

Mac address auto learning and auto aging

LED indicators for monitoring power, link/activity, speed

Management

Unmanaged (Plug and Play)



Support IEEE802.3af/3at (30W each port)



Auto-Negotiation



Auto detect MDI/MDIX



Half-duplex & Full-duplex Mode



150m Transmission distance



Fast Ethernet Switch (10/100Mbps)



PAP Switch (Plug and Play)

■ TECHNICAL SPECIFICATION

Model No.	SW-UNM-4FE1FE-4POE
Product description	4 Ports 10/100Mbps PoE + 1 port 10/100Mbps Ethernet Switch
Chipset	IP175G + PD69104B
10/100Mbps RJ45 Ports	5
10/100/1000Mbps RJ45 Ports	NA
1000Mbps SFP Ports	NA
Console Port	NA
PoE Ports	4
Standards	IEEE802.3u, IEEE802.3u, IEEE802.3x, IEEE802.3az, IEEE802.3at, IEEE802.3af
Switching Fabric Capacity	1Gbps
Mac Address Table	2K
Buffer	96Kbps
Jumbo Frame	1.536KByte
IEEE802.3af	\checkmark
IEEE802.3at	\checkmark
Power Supply	DC 51V (65W)
Max PoE Output Power	62.5W
Housing	Metal
Dimension	80 x 90 x 21mm