

SW-UNM-8FE



SW-UNM-9FE



SW-UNM-16FE



SW-UNM-24FE



Network Switches

FEATURES

Port Features

Auto negotiation and auto MDI/MDIX

Switching Features

Store and forward switching method

Full duplex flow control and half duplex backpressure

Mac address auto learning and auto aging

LED indicators for monitoring power, link/activity, speed

Management

Unmanaged (Plug and Play)



Auto-Negotiation



Auto detect MDI/MDIX



Half-duplex & Full-duplex Mode



150m Transmission distance



PAP Switch (Plug and Play)

TECHNICAL SPECIFICATION

Model No.	SW-UNM-8FE	SW-UNM-9FE	SW-UNM-16FE	SW-UNM-24FE
product description	SOHO 8 Fast Ethernet Ports	SOHO 8 Fast Ethernet Ports	16 Fast Ethernet Switch	24 Fast Ethernet Ports
Chipset	IP178G		IP1717+IP108A	IP1725LF
10/100Mbps RJ45 Ports	8	9	16	24
10/100/1000Mbps RJ45 Ports			NA	
1000Mbps SFP Ports			NA	
Console Port			NA	
PoE Ports			NA	
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x		IEEE802.3, 10Base-T, IEEE802.3u 100Base-TX	
Switching Fabric Capacity	1.6Gbps		3.2Gbps	4.8G
Mac Address Table	1K		4K	8K
Buffer	96Kbps			4.1Mbps
Jumbo Frame	9216KByte			10KByte
IEEE802.3af			NA	
IEEE802.3at			NA	
Power Supply	DC 5V/0.55A		Input: 100-240V 50-60Hz 0.3A Consume: 7 W (MAX)	Input: 100-240V 50-60Hz 0.6A Consume: 6 W(MAX)
Max PoE Output Power			NA	
Housing	Plastic (Desktop)			Metal Rack Mount
Dimension	115.7 X 54 X 1.0 mm			440 x 208 x 44 mm