

Managed Switches

SW-MNG-24GE4GC-24POE



FEATURES

Port Features

Auto negotiation and auto MDI/MDIX

Switching Features

Store and forward switching method

Full duplex flow control and half duplex backpressure

Mac address auto learning and auto aging

LED indicators for monitoring power, link/activity, speed

Supports IEEE802.1Q VLAN, 4K VLAN Table

Support QoS, Port Mirroring, Link Aggregation Protocol

Management

Web-Based Management Supports

Support SNMP/RMON/TELENET

Console Port



Auto-Negotiation



Auto detect MDI/MDIX



Half-duplex & Full-duplex Mode



150m Transmission distance



Giga Ethernet Switch



Web Management



Qos (Quality of service)



Port Isolation



Bandwidth Control

TECHNICAL SPECIFICATION

Model No.

SW-MNG-24GE4GC-24POE

Product description

Managed 24 Giga Ethernet Ports POE+ 4 Ports Giga COMBO

Chipset

RTL8332L + RTL8208L + RTL8214B

10/100Mbps RJ45 Ports

NA

10/100/1000Mbps RJ45 Ports

24

1000Mbps SFP Ports

4

10Gbps SFP ports

NA

Console Port

1

PoE Ports

24

Standards

IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az, IEEE802.3x, IEEE802.3z, IEEE802.3ad, IEEE802.1P, IEEE802.1Q, IEEE802.1s, IEEE802.1d, IEEE802.1w, IEEE802.3af, IEEE802.3at

Switching Fabric Capacity

56Gbps

Mac Address Table

8K

Buffer

4.1Mb

Jumbo Frame

10KByte

IEEE802.3af

✓

IEEE802.3at

✓

Power Supply

AC 100V-240V 50/60HZ

Max PoE Output Power

380 W

Housing

Metal Rack Mount

Dimension

440 x 208 x 44 mm