



Portable Wireless IP Phone

IPTEL-24AWF



FEATURES

- 2 SIP accounts.
- 2.4-inch color LCD.
- HD sound quality: HD earpiece, HD speaker, support 3.5mm HD headset.
- HD high-definition audio: microphone echo cancellation, noise reduction technology.
- Equipped with Linux system, dual-band Wi-Fi (2.4 G& 5 G) 802.11 a/b/g/n module.
- Supporting remote locations Roaming.



Personalized customized ringtones



Type-C Power connector cable



Support 3.5mm earphones



Large 2.4-inch LCD true-color screen



Wifi 2.4G & 5GHz



3000mA Rechargeable battery

TECHNICAL SPECIFICATION

Model No.	IPTEL-24AWF
Account	Support 2 SIP accounts
Physical Interface	3.5mm headphone jack, Type-C
Screen	2.4" (240×320) TFT color screen
Handset Size	160mm*55mm*24mm
Charging Base Size	116mm*100mm*106mm
Power Supply	Universal power adapter, input: 100-240VAC; output: +5VDC, 1A (5W) 3000mA Li-ion battery, talk time 10h
Fall Resistance	1.3m Drop resistance
Working Temperature	0~45°C, 10~90% (non-condensing)
Storage Temperature	-20~60°C, 10~90% (no condensation)
Operating System	Linux
Language	Support 17 languages (Simplified Chinese, Traditional Chinese, English, Turkish, Korean, Russian, French, Italian, German, Polish, Portuguese, Thai, Hindi, Arabic, Japanese, Spanish, Vietnamese language)
Protocol/Standard	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP, STUN, SIMPLE, LDAP, TR-069 , 802.1x, TLS,SRTP, Ipv6, LLDP-ME
Audio Features	High-fidelity sound quality: HD handle, HD hands-free, HD headset
WiFi	Built-in dual-band Wi-Fi (2.4GHz&5GHz) 802.11a/b/g/n
Security Protection	User and administrator-level passwords, based on MD5 and MD5-sess authentication, 256-bit AES security profile, SRTP, TLS call
QoS	802.11e and Layer 3 QoS (ToS, DiffServ, MPLS), Upgrade/configuration: upgrade firmware via TFTP / HTTP / HTTPS, PnP automatic deployment, web upload firmware upgrade, use TR-069 or AES encrypted XML configuration file for large-scale deployment