

# Patch Panel

## FO-REP-PAT3

### DESCRIPTION:

- 1U and 2U versions (12, 24, 36, and 48 port capacity).
- Smooth and convenient mechanical sliding system.
- Manages small & large quantities of fiber with a high packing density.
- Cable glands to secure the incoming fiber, allows min movement.
- Fiber guide tubes to protect and direct the fibers to the cassettes in a professional way.
- Easy to maintain and extend.
- Minimum bend radius of fibers and strain relief for all entry cables.
- Fiber bend radius control of 35mm.
- Capacity of up to 48 ports.
- All known connector types such as SC, FC, ST, E2000, LC, MU etc.
- 5 Years warranty.



### APPLICATIONS:

- FTTX applications, Datacenter and LAN & WAN projects.

MODEL	FO-REP-PAT3-24S-B	FO-REP-PAT3-12D-B
Description	Patch Panel with Front Panel 24Pcs SC Simplex Adaptor	Patch Panel with Front Panel 12Pcs SC Duplex Adaptor
Dimensions	(19") 465 mm (W) x 265 mm (D) x 1U (H)	
Material	Mild Steel	
Color	Powder coat RAL 7035 or RAL9005	
Weight	2Kg	
Maximum Port Capacity	48 Ports	
	*Color: Light Grey or Black	*The body of panel is easy to be pulled and pushed Tray
		*Patch Panel with 2pcs of splicing Tray