

Managed Switches

SW-3MNG-24GE4TGSFP



FEATURES

Layer 2 Features:

4K VLAN Table, 16K MAC table, QoS, port-isolation, link aggregation protocol, link-layer discovery protocol, spanning tree protocol.

DHCP server/client.

Multicast Management:

Support IGMP Snooping V1/V2/V3.

Layer 3 Features:

Routing between different subnets, different VLANs and static routing.

Routing Protocols: RIP, OSPF.

Security Features:

Access list (L2-L4), port-security

Management:

Web-based management supports.

Support SNMP/RMON/TELNET/SSH; Console port, stacking.



Auto-Negotiation



Giga Ethernet Switch



Port Isolation



250m Transmission Distance



2 Years Warranty



Web Management



Qos (Quality of service)



Bandwidth Control



10 Giga SFP



24/7 Technical Support

TECHNICAL SPECIFICATION

MODEL No.

SW-3MNG-24GE4TGSFP

Product Description	Managed 24 Giga Ethernet Ports + 4 Ports 10 Giga SFP
Chipsets Origin	Taiwanese
10/100Mbps RJ45 Ports	NA
10/100/1000Mbps RJ45 Ports	24
1000Mbps SFP Ports	NA
10Gbps SFP ports	4
Console Port	1
PoE Ports	NA
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z, IEEE802.3ad, IEEE802.3az, IEEE802.1q, IEEE802.1p, IEEE802.1s, IEEE802.1d, IEEE802.1w, IEEE802.1x, IEEE802.1ad, IEEE802.1ab, IEEE802.3ae
Switching Fabric Capacity	128Gbps
MAC Address Table	16K
Buffer	12Mb
Jumbo Frame	12KBytes
IEEE802.3af	NA
IEEE802.3at	NA
Operating Temperature	0°C ~50°C
Power Supply	AC 100V-240V 50/60HZ
Max PoE Output Power	NA
Housing	Rack Mount
Material	Metal
Dimensions	440 x 208 x 44 mm