

Network Switch

SW-3MNG-24TGSFP-2HGSFP



FEATURES

Layer 2 Features:

4K VLAN Table, 16K MAC table, QoS, port-isolation, link aggregation protocol, link layer discovery protocol, spanning tree protocol.

DHCP server/client.

Multicast Management:

Support IGMP Snooping V1/V2/V3.

Layer 3 Features:

Routing between different subnets, different VLANs and static routing.

Routing protocols: RIP, OSPF.

Security Features:

Access list (L2-L4), port-security.

Management:

Web-based management supports.

Support SNMP/RMON/TELNET/SSH; Console port.



Auto-Negotiation



Qos (Quality of Service)



Bandwidth Control



Core Switch



2 Years Warranty



10 Giga SFP



100 Giga SFP



Web Management



Port Isolation



24/7 Technical Support

TECHNICAL SPECIFICATION

MODEL No.	SW-3MNG-24TGSFP-2HGSFP
Product Description	Layer 3, Managed 24 Ten Giga Giga Ethernet Ports + 2 Ports 100 Giga SFP
Chipsets Origin	US
10/100/1000Mbps RJ45 Ports	NA
1000Mbps Combo Ports	NA
10Gbps SFP Ports	24
100Gbps SFP ports	2
PoE Ports	NA
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z, IEEE802.3ad, IEEE802.3az, IEEE802.1q, IEEE802.1p, IEEE802.1s, IEEE802.1d, IEEE802.1w, IEEE802.1x, IEEE802.1ad, IEEE802.1ab, IEEE802.3ae, IEEE802.3bm
Switching Fabric Capacity	880Gbps
MAC Address Table	32K
Buffer	72Mbit
Working Temperature	-10°C ~ 50°C
Storage Temperature	-40°C ~ 85°C
Power Supply	AC100-240V, 50/60Hz
Max PoE Output Power	NA
Material	Metal
Housing	Rackmount
Dimensions	440mm*390mm*44mm