

Managed Switches



SW-MNG-24GE4GSFP-24POE



FEATURES

PoE Features:

Support active IEEE 802.3af/at for new POE devices and static mode for traditional POE devices.

PoE overload and short circuit protection, sensitive POE ports.

Layer 2 Features:

4K VLAN Table, 8K MAC table, QoS, port-isolation, link aggregation protocol, link-layer discovery protocol, spanning tree protocol.

DHCP server/client.

Multicast Management:

Support IGMP Snooping V1/V2/V3.

Security Features:

Access list (L2-L4), port-security

Management:

Web-based management supports.

Support SNMP/RMON/TELNET/SSH; Console port.



PoE Overload Protection



2 Years Warranty



PoE Short Circuit Protection



250m Transmission Distance



Giga Ethernet Switch



4 Giga SFP Ports



Web Management



Port Isolation



Bandwidth Control



24/7 Technical Support

TECHNICAL SPECIFICATION

MODEL No.	SW-MNG-24GE4GSFP-24POE
Product Description	Managed 24 Giga Ethernet Ports POE+ 4 Giga SFP Ports
Chipsets Origin	Taiwanese
10/100Mbps RJ45 Ports	NA
10/100/1000Mbps RJ45 Ports	24
1000Mbps SFP Ports	4
Console Port	1
PoE Ports	24
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z, IEEE802.3ad, IEEE802.3az, IEEE802.1q, IEEE802.1p, IEEE802.1s, IEEE802.1d, IEEE802.1w, IEEE802.1x, IEEE802.1ad, IEEE802.1ab, IEEE802.3af/at
Switching Fabric Capacity	56Gbps
MAC Address Table	8K
Buffer	4.1Mb
Jumbo Frame	10KByte
IEEE802.3af	√
IEEE802.3at	√
Power Supply	AC 100V-240V 50/60HZ
Operating Temperature	0°C ~50°C
Max PoE Output Power	370W
Housing	Rack Mount
Material	Metal
Dimensions	440 x 220x 44mm