

Unmanaged Switches

SW-UNM-16FE2GC-16POE



FEATURES

Port Features:

Auto-negotiation and auto MDI/MDIX.

Switching Features:

Store and forward switching method.

Full duplex flow control and half-duplex backpressure.

MAC address auto-learning and auto aging.

LED indicators for monitoring power, link/activity, speed.

Unmanaged (Plug and Play).



PoE Short Circuit Protection



Auto-Negotiation



CCTV Mode



Giga Combo



PD Alive Check



PoE Overload Protection



Fast Ethernet Switch



PAP Switch (Plug and Play)



1 Year Warranty



24/7 Technical Support

TECHNICAL SPECIFICATION

MODEL No.	SW-UNM-16FE2GC-16POE
Product Description	16 Fast Ethernet PoE Ports + 2 Giga Combo
Chipsets Origin	Taiwanese
Mode	Default, VLAN, & CCTV Mode
10/100Mbps RJ45 Ports	16
10/100/1000Mbps RJ45 Ports	2
1000Mbps SFP Ports	2
Console Port	NA
PoE Ports	16
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z, IEEE802.3az, IEEE802.3af & IEEE802.3at
Switching Fabric Capacity	7.2Gbps
MAC Address Table	8K
Buffer	4.1Mb
Jumbo Frame	10KByte
IEEE802.3af	✓
IEEE802.3at	✓
Power Supply	AC 100V-240V 50/60HZ (390W)
Operating Temperature	0°C ~50°C
Max PoE Output Power	370W
Housing	Rack Mount
Material	Metal
Dimensions	440 x 208 x 44 mm